



ADDENDUM No. 1  
Request for Competitive Sealed Proposals (CSP)  
19CSP088 Akins High School Weight Room & Athletic  
Field Improvements

December 20, 2018

Item 1: Updates to Drawings and Specifications

Item 1:

Please see attached Exhibit ^A\_ for modifications to the original Drawings and Specifications

Exhibit "A"



ADDENDUM NO. 1, Dated: December 20, 2018  
IRRIGATION ALLOWANCE  
EXHIBIT 'A'

---

**Project Title:** Akins High School Weight Room & Athletic Field Improvements

**Function:** Building e 1 [ ( A ) 4. 9 ( - - 3. 6 e 1 T 22 - 1. 21741T j - T j 0 1

---

---

0 1n 00  
06 6 id

HHK&

HHn

1n

0

11

10

11

11

- 11

1

XXXXXXXXXXXXXXXXXXXX



06 6 10

0000

00

00

3 00

A 0000  
00000000  
00

000000

000

3 00

S

A 00  
0000

1 1 0

0000

00

0 0 0 0 0 0  
0 0 0 0 0 0

1 00  
00

00

00

, 0000

00

## SECTION 096623 – RESILIENT RUBBER ATHLETIC FLOORING

### PART 1- GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Resilient (rubber) Athletic Flooring.

#### 1.3 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Samples for Initial Selection: For each type of product indicated.
- C. Samples for Verification: For each type of product indicated, in manufacturer's standard size samples of each resilient product color, texture, and pattern required.
- D. Product Schedule: For resilient rubber products. Use same designations indicated on Drawings

#### 1.4 QUALITY ASSURANCE

- A. Mockups: Provide resilient products with mockups as specified in other Sections.

#### 1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store resilient products and installation materials in dry spaces protected from the weather, with ambient temperatures maintained within range recommended by the manufacturer

#### 1.6 PROJECT CONDITIONS

- A. Install resilient rubber products after other finishing operations, including painting, have been completed.
- B. Maintain ambient temperatures within range recommended by manufacturer during the following time periods:
  - 1. 48 hours before installation.
  - 2. During installation.

3. 48 hours after installation.
- C. Maintain the ambient relative humidity between 40% and 60% during installation.
- D. Until Substantial Completion, maintain ambient temperatures within range recommended by manufacturer

## PART 2- PRODUCTS

### 2.1 PERFORMANCE REQUIREMENTS

- A. Basis of Design Product: Rubber Flooring Inc., 1/2 Rubber Gym Tiles
  1. Physical Properties Testing by a qualified testing agency. Identify products with appropriate markings of applicable testing agency
    - a. Durometer Shore A: ASTM D-2240, Result 63
    - b. Tensile Strength: ASTM D-412, Result 800
    - c. Elongation %: ASTM D-412, Result 275.
    - d. Test Resistance: ASTM D-24, Result 135.
    - e. Coefficient of Friction: ASTM C1028, Result .85 dry, .95 wet.









