21RFP057 Internet Firewall Replacements
Attachment B
Installation / Configuration Instructions
Sample

Firewall Installation and Configuration Guide
Version 01, 11/14

4500X base system module	**WS-C4500X-32SFP+**
module 2	

4500X base system	**WS-C4500X-32SFP+ with module2**
module 1	**WS-C4500X-32SFP+**
module 2	**C4KX-NM-8SFP+**

2.2 Assemble, install and label

1) Install and secure Line Card modules and power supplies to the chassis according to design. Note that the switch will have dual power supplies (PS).
2) DO NOT insert the Optics yet; these parts are easy to damage in transit, and should only be installed after the hardware has been racked and installed at the school campus.
3) Switch labeling: label the switch as xyzc4X01, where xyz is the campus number.
4) Asset tag placement: according to AISD WAN Network Labeling Standard.
5) Power cable labeling according to AISD WAN Network Labeling Standard.

2.3 Power on and check the switch

1) Check and verify the switch power-on self-test (POST) is successful. Check0912 0 612 792 reW*nBT/F4

The first one is a pre-config file consisting of a few commands that are intended to be copy-and-pasted directly from that file into the switch in global configuration mode. This pre-config file prepares the switch to be configured from the master config file.
The other one is the master configuration file, it will be copied to the startup configuration of the switch via USB flash or TFTP. **Don't copy-and-paste the master config to the switch!**

A. Copy the appropriate pre-config file to the switch

1) Load the appropriate pre-config file titled <switch-num>c4X01

Optical Receive Power > -6dBm

NOTE: If you need to start over from scratch and reload a completely new configuration on a Cat45XX, the following commands may be used to thoroughly delete the current configuration and return to factory defaults.

erase startup-config

erase cat4000_flash:

delete nvram: ifIndex-table.gz

crypto key zeroize rsa -rsakey

4.1 3850 Switch Hardware Information

Switch model: WS-C3850-48P-S
Switch power Supply: PWR-C1-715WAC=
Switch module: C3850-NM-2-10G

Catalyst 3850 Stack Power cable type:

1) CAB-SPWR-30CM: 0.3 meter
2) CAB-SPWR-150CM: 1.5 meter

Catalyst 3850 Stack Data cable type:

1) STACK-T1-50CM: 0.3 meter

9) Check all the switch LED indicators and make sure there are no abnormal conditions.
10)

6) on each switch will illuminate, indicating the stack number that is assigned to each switch.

11) After checking the number on the switches, renumber them as appropriate such that the first switch (top) in the stack (with the network module) is numbered 1 and last switch (bottom, also with a network module) is numbered with the highest number in the stack. For example, in a stack of four switches the highest-numbered switch in the stack (which also has the other 10G module) should be numbered 4.

```
Switch# show switch
Switch# switch <current-number> renumber <new-number>
```

Note: After the above command is entered, the numbers will NOT change until after a reboot. However, you can save time by not rebooting yet.

12) After the switches have been renumbered, but before rebooting, set the stack priority for

been renumbered, so continue using the old numbers:

```
Switch# switch <current-number-of-top-switch> priority 10
Switch# switch <current-number-of-bottom-switch> priority 9
Switch# write
```

13) Label or tag each switch according to the switch number learned in the previous step. You may not wish to apply the final label to the first and last switch yet, since the C3850-NM-2-10G modules are not yet installed, and the label will end up being affixed to the bezel of those modules.

2.

1) Load the appropriate pre-config file titled <switch-num><closet>38<num>_pre.cfg (e.g. 252A3801_pre.cfg) into a text editor.
2) Select all the text in the file and copy it to the clipboard
3) Enter enable mode on the switch and paste the clipboard contents in. This will set up the switch member priorities, vtp information, and create a crypto key.

4.4 Installation and Configuration at the School C

AISD Whatsup Gold
Active Monitor Name

	Action	Check
Connectivity Testing (Wireless)		Set your laptop to connect to AISD wireless network guest. Verify that the laptop gets a DHCP address, and can access the network via wireless.

3) Enter configuration mode on the switch and paste the clipboard contents in. This will

Action	Command	Verification	OK?
Check that master config file was copied successfully via TFTP	**Show ip int brief** **Show int status** **Show ip default-gateway**	There should be one management IP interface set up on VLAN 501, with the correct IP address set Configured uplink switchports should have correct descriptions. User access ports should be defaulted to VLAN 305. There should be one default gateway configured	
Asset tag set	**show snmp contact**	Should be set to AISD Asset Tag number(s)	
Configuration is saved	**copy run start** <or> **wr mem**	Save it once more to be sure	

5.3 Installation and configuration at the School Campus

1) Port assignment and Patch
   Gi0/1-2: for Access ports
   Gi0/3-4: for devices requires PoE power.
   Gi0/9-24: for end user equipment without PoE
   Gi0/27: for Active fiber uplink to 4500X switch.

2) Verify that the fiber link will come up before mounting the switch.
   a. There may be issues with the links from the portables.
   b. Connect the uplink cable to switch port Gi0/27
   c. If the link comes up, make a console connection, ping the 4500X
   d. Connect to an access port and verify internet access is working.
   e. From the 4500X console, check this link for interface errors which may indicate link problems.
   f. If the link does not come up, use the LX/LH optics with mode conditioning patch cables to make the link. Then repeat steps c-e.
3) Mount the switch to the portable classroom location according to AISD Guideline.
4) Connect the uplink cable to switch port Gi0/27
5) Set

For Cisco AP:

(config)# default interface g0/2

21) (config)# int g0/2

NOTE:

erase startupconfig

delete flash:vlan.dat

crypto key zeroize rsa -rsakey

SSH credentials:
Username:your ACS user name
Password: your ACS password

Device credentials:
Enable password: cisco
Console password: cisco